

BENOTTI BLADE SL

DREHMOMENTEMPFEHLUNGEN

TORQUE RECOMMENDATIONS

BENOTTI
by ax-lightness



Produkt Product	Empfohlenes Drehmoment Recommended torque
1 Bremse vorne Front brake	5 bis/to max. 6 Nm
2 Bremse hinten Rear brake	5 bis/to max. 6 Nm
3 Flaschenhalterschrauben Bottle cage screws	1,5 bis/to max. 2 Nm
4 Vorbauklemmung Stem steerer clamping	5 bis/to max. 6 Nm
5 Sattelklemmung Saddle clamping	7 bis/to max. 8 Nm
6 Sattelstützenklemme Seatpost clamp	5 bis/to max. 6 Nm
7 Schalttauge UDH Rear derailleur hanger	max. 25 Nm
8 Schaltwerk Rear derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
9 Umwerfer Front derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
10 Computerhalterung Cockpit Computer mount cockpit	2 Nm + LOCTITE Schraubensicherung/ LOCTITE screw lock
Steckachsen vorne / hinten Thru-axle front /rear	10 Nm empfohlen/recommended



max. Reifendruck / max. tire pressure

ax-lightness ULTRA 35CX	28-622: 7.0 bar / 32-622: 5.0 bar 40-622: 3.5 bar / 45-622: 2.8 bar
ax-lightness ULTRA 45CX	28-622: 7.0 bar / 32-622: 5.0 bar 40-622: 3.5 bar / 45-622: 2.8 bar