

# FUOCO Gravel Race

## DREHMOMENTEMPFEHLUNGEN TORQUE RECOMMENDATIONS

**BENOTTI**  
by ax-lightness



|    | Produkt<br>Product                                   | Empfohlenes Drehmoment<br>Recommended torque                      |
|----|------------------------------------------------------|-------------------------------------------------------------------|
| 1  | Bremse vorne<br>Front brake                          | 5 bis/to max. 6 Nm                                                |
| 2  | Bremse hinten<br>Rear brake                          | 5 bis/to max. 6 Nm                                                |
| 3  | Flaschenhalterschrauben<br>Bottle cage screws        | 1,5 bis/to max. 2 Nm                                              |
| 4  | Lenkerklemmung<br>Bar clamping                       | Verschraubung/tightening<br>5 bis/to max. 6 Nm                    |
| 5  | Vorbauklemmung<br>Stem steerer clamping              | 5 bis/to max. 6 Nm                                                |
| 6  | Sattelklemmung<br>Saddle clamping                    | 7 bis/to max. 8 Nm                                                |
| 7  | Sattelstützenklemme<br>Seatpost clamp                | 4 bis/to max. 6 Nm                                                |
| 8  | Schaltauge UDH<br>Rear derailleur hanger             | max. 25 Nm                                                        |
| 9  | Schaltwerk<br>Rear derailleur                        | Herstellerangaben befolgen/<br>follow manufacturer's instructions |
| 10 | Umwerfer<br>Front derailleur                         | Herstellerangaben befolgen/<br>follow manufacturer's instructions |
|    | Steckachsen vorne / hinten<br>Thru-axle front / rear | 10 Nm empfohlen/recommended                                       |



### max. Reifendruck / max. tire pressure

|                                           |                                                                       |
|-------------------------------------------|-----------------------------------------------------------------------|
| ax-lightness SELECTION 35C<br>CX Disc     | 28-622: 7.0 bar / 32-622: 5.0 bar<br>40-622: 3.5 bar / 45-622: 2.8 ba |
| ax-lightness ULTRA 45C CX<br>Disc Ceramic | 28-622: 7.0 bar / 32-622: 5.0 bar<br>40-622: 3.5 bar / 45-622: 2.8 ba |