

FUOCO Gravel

DREHMOMENTEMPFEHLUNGEN TORQUE RECOMMENDATIONS

BENOTTI
by ax-lightness



Produkt Product	Empfohlenes Drehmoment Recommended torque
1 Bremse vorne Front brake	5 bis/to max. 6 Nm
2 Bremse hinten Rear brake	5 bis/to max. 6 Nm
3 Flaschenhalterschrauben Bottle cage screws	1,5 bis/to max. 2 Nm
4 Lenkerklemmung Bar clamping	Verschraubung/tightening 5 Nm
5 Vorbauklemmung Stem steerer clamping	5 Nm
6 Sattelklemmung Saddle clamping	7 bis/to max. 8 Nm
7 Sattelstützenklemme Seatpost clamp	4 Nm
8 Schalttauge Rear derailleur hanger	max. 20 Nm
9 Schaltwerk Rear derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
10 Umwerfer Front derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
Steckachsen vorne / hinten Thru-axle front / rear	10 Nm empfohlen/recommended



max. Reifendruck / max. tire pressure

DT Swiss G1800 Spline:	Herstellerangaben befolgen/ follow manufacturer's instructions
engage 35C Evo Carbon Disc:	28-622: 7.0 bar / 32-622: 5.0 bar 40-622: 3.5 bar / 45-622: 2.8 bar
engage 45C Evo Carbon Disc:	25-622: 8.0 bar / 28-622: 7.0 bar 32-622: 5.0 bar