

FUOCO AERO SL

DREHMOMENTEMPFEHLUNGEN TORQUE RECOMMENDATIONS

BENOTTI
by ax-lightness



Produkt Product	Empfohlenes & max. Drehmoment Recommended & max. torque
1 Bremse vorne Front brake	5 bis/to max. 6 Nm
2 Bremse hinten Rear brake	5 bis/to max. 6 Nm
3 Flaschenhalterschrauben Bottle cage screws	1,5 bis/to max. 2 Nm
4 Vorbauklemmung Stem steerer clamping	5 Nm
5 Sattelklemmung Saddle clamping	7 bis/to max. 8 Nm
6 Sattelstützenklemme Seatpost clamp	6 Nm
7 Schalttauge Rear derailleur hanger	max. 20 Nm
8 Schaltwerk Rear derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
9 Umwerfer Front derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
10 Computerhalterung Cockpit Computer mount cockpit	2 Nm + LOCTITE Schraubensicherung/ LOCTITE screw lock
Steckachsen vorne / hinten Thru-axle front / rear	empfohlen/recommended: 10 Nm



max. Reifendruck / max. tire pressure

DT Swiss P1800 Spline:	Herstellerangaben befolgen/ follow manufacturer's instructions
ax-lightness/engage 45C Evo	25-622: 8.0 bar / 28-622: 7.0 bar
Disc Carbon:	32-622: 5.0 bar