

BENOTTI BLADE EDR

DREHMOMENTEMPFEHLUNGEN

TORQUE RECOMMENDATIONS

BENOTTI
by ax-lightness

RennRad
MAGAZIN

PREIS-LEISTUNG

4/2025



	Produkt Product	Empfohlenes Drehmoment Recommended torque
1	Bremse vorne Front brake	5 bis/to max. 6 Nm
2	Bremse hinten Rear brake	5 bis/to max. 6 Nm
3	Flaschenhalterschrauben Bottle cage screws	1,5 bis/to max. 2 Nm
4	Lenkerklemmung Bar clamping	Verschraubung/tightening 5 bis/to max. 6 Nm
5	Vorbauklemmung Stem steerer clamping	5 bis/to max. 6 Nm
6	Sattelklemmung Saddle clamping	7 bis/to max. 8 Nm
7	Sattelstützenklemme Seatpost clamp	8 Nm empfohlen/recommended
8	Schaltauge UDH Rear derailleur hanger	max. 25 Nm
9	Schaltwerk Rear derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
10	Umwerfer Front derailleur	Herstellerangaben befolgen/ follow manufacturer's instructions
	Steckachsen vorne / hinten Thru-axle front /rear	10 Nm empfohlen/recommended



max. Reifendruck / max. tire pressure

ax-lightness SELECTION 35C CX Disc	28-622: 7.0 bar / 32-622: 5.0 bar 40-622: 3.5 bar / 45-622: 2.8 bar
ax-lightness ULTRA 45C CX Disc Ceramic	28-622: 7.0 bar / 32-622: 5.0 bar 40-622: 3.5 bar / 45-622: 2,8 bar